

## Aqualift F XL, 200 L lift. stat. Mono, SPF 1400-S3, Backflow preventer



### Article information

Item no.: 11004  
GTIN: 4026092056714  
Price group: 50

### Advantages

- Different performance classes available
- Pressure sensor for reliable pneumatic level measurement
- Maximum operating reliability due to intelligent control unit (Duo)

### Description

The lifting station for faecal and faecal-free wastewater is equipped with one or two submersible pumps and a backflow preventer. The collection tank made of permanently resistant polymer (PE) offers universal connection options and has a screwed access cover.

#### Variant

Type of system: Single unit  
Shut-off valve: without shut-off valve  
Backflow preventer: integrated  
Pressure pipe connection: vertical

#### General characteristics

Colour: black  
Standard: EN 12050-1  
Type of wastewater: with sewage  
Installation situation: free-standing installation  
System type: Mono

#### Dimensions

Net weight: 105,39 kg  
Gross weight: 125,39 kg  
Packaging dimension: length  
Packaging dimension: width  
Packaging dimension: height

#### Tank/drain body

Tank volume: 200 l

Pumping device  
Pump:  
Number of pumps:  
Operating mode:  
Impeller type:  
Free passage:  
Length of mains cable for pump:

SPF 1400-S3  
1  
S3 - 50 %  
Multi-vane impeller  
40 mm  
5 m

Control  
Control unit:  
Level measurement instrument:  
Type of level measurement:  
Mains frequency:  
Operating voltage:

Comfort  
Immersion pipe  
pneumatic  
50 Hz  
230 V