

Lifting stati. Aqualift F XL 300l Duo, SPF 1400-S3, Cast-iron shut-off val.



Article information

Item no.: 11016
GTIN: 4026092056837
Price group: 50

Advantages

- Different performance classes available
- Pressure sensor for reliable pneumatic level measurement
- Maximum operating reliability due to intelligent control unit (Duo)

Description

The lifting station for faecal and faecal-free wastewater is equipped with one or two submersible pumps and a backflow preventer. The collection tank made of permanently resistant polymer (PE) offers universal connection options and has a screwed access cover.

Variant

Type of system: duo pump
Shut-off valve: Shut-off valve made of cast iron
Pressure pipe connection: vertical

General characteristics

Colour: black
Standard: EN 12050-1
Type of wastewater: with sewage
Installation situation: free-standing installation
System type: Duo

Dimensions

Net weight: 195,77 kg
Gross weight: 215,77 kg
Packaging dimension: length
Packaging dimension: width
Packaging dimension: height

Tank/drain body

Tank volume: 300 l

Pumping device

Pump: SPF 1400-S3
Number of pumps: 2
Operating mode: S3 - 50 %
Impeller type: Multi-vane impeller
Free passage: 40 mm
Length of mains cable for pump: 5 m

Control
Control unit: Comfort
Level measurement instrument: Immersion pipe
Type of level measurement: pneumatic
Mains frequency: 50 Hz
Operating voltage: 230 V