

## Lifting stati. Aqualift F XL 300l Duo, SPF 1400-S3, Cast-iron shut-off val.



## **Article information**

Item no.: 11016

GTIN: 4026092056837

Price group: 50

## **Advantages**

- Different performance classes available
- Pressure sensor for reliable pneumatic level measurement
- Maximum operating reliability due to intelligent control unit (Duo)

## **Description**

The lifting station for faecal and faecal-free wastewater is equipped with one or two submersible pumps and a backflow preventer. The collection tank made of permanently resistant polymer (PE) offers universal connection options and has a screwed access cover.

Variant

Type of system: duo pump

Shut-off valve: Shut-off valve made of cast iron

Pressure pipe connection: vertical

General characteristics

Colour: black
Standard: EN 12050-1
Type of wastewater: with sewage

Installation situation: free-standing installation

System type: Duo

**Dimensions** 

Net weight: 195,77 kg
Gross weight: 215,77 kg
Packaging dimension: length
Packaging dimension: width
Packaging dimension: height

Tank/drain body

Tank volume: 300 l

Pumping device



Pump: SPF 1400-S3

Number of pumps: 2

Operating mode: S3 - 50 %

Impeller type: Multi-vane impeller

Free passage: 40 mm Length of mains cable for pump: 5 m

Control

Control unit: Comfort

Level measurement instrument: Immersion pipe
Type of level measurement: pneumatic
Mains frequency: 50 Hz
Operating voltage: 230 V