

Lifting stati. Aqualift F XL 300l Duo, SPF 1500-S3, Backflow preventer



Article information

Item no.: 11032
GTIN: 4026092056998
Price group: 50

Advantages

- Different performance classes available
- Pressure sensor for reliable pneumatic level measurement
- Maximum operating reliability due to intelligent control unit (Duo)

Description

The lifting station for faecal and faecal-free wastewater is equipped with one or two submersible pumps and a backflow preventer. The collection tank made of permanently resistant polymer (PE) offers universal connection options and has a screwed access cover.

Variant

Type of system: duo pump
Shut-off valve: without shut-off valve
Backflow preventer: integrated
Pressure pipe connection: vertical

General characteristics

Colour: black
Standard: EN 12050-1
Type of wastewater: with sewage
Installation situation: free-standing installation
System type: Duo

Dimensions

Net weight: 182,57 kg
Gross weight: 202,57 kg
Packaging dimension: length
Packaging dimension: width
Packaging dimension: height

Tank/drain body

Distance from centre of outlet pipe to tank bottom: 609 mm

Tank volume: 300 l

Pumping device

Pump:

Number of pumps:

Operating mode:

Impeller type:

Free passage:

Length of mains cable for pump:

SPF 1500-S3

2

S3 - 50 %

Multi-vane impeller

40 mm

5 m

Control

Control unit:

Level measurement instrument:

Type of level measurement:

Mains frequency:

Operating voltage:

Comfort

Immersion pipe

pneumatic

50 Hz

400 V