

## Aqualift F XL, 450 L lift. stat. Duo, SPF 3000-S3, Backflow preventer



### Article information

Item no.: 11056  
GTIN: 4026092057230  
Price group: 50

### Advantages

- Different performance classes available
- Pressure sensor for reliable pneumatic level measurement
- Maximum operating reliability due to intelligent control unit (Duo)

### Description

The lifting station for faecal and faecal-free wastewater is equipped with one or two submersible pumps and a backflow preventer. The collection tank made of permanently resistant polymer (PE) offers universal connection options and has a screwed access cover.

#### Variant

Type of system: duo pump  
Shut-off valve: without shut-off valve  
Pressure pipe connection: vertical

#### General characteristics

Colour: black  
Standard: EN 12050-1  
Type of wastewater: with sewage  
Installation situation: free-standing installation  
System type: Duo

#### Dimensions

Net weight: 188,73 kg  
Gross weight: 208,73 kg  
Packaging dimension: length  
Packaging dimension: width  
Packaging dimension: height

#### Tank/drain body

Tank volume: 450 l

#### Pumping device

Pump: SPF 3000-S3

Number of pumps: 2  
Operating mode: S3 - 50 %  
Impeller type: Multi-vane impeller  
Free passage: 40 mm  
Length of mains cable for pump: 5 m

Control  
Control unit: Comfort  
Level measurement instrument: Immersion pipe  
Type of level measurement: pneumatic  
Mains frequency: 50 Hz  
Operating voltage: 400 V