

Lifting stati. Aqualift F XL 300l Duo, SPF 5500-S3



Article information

Item no.: 11078
GTIN: 4026092057452
Price group: 50

Advantages

- Different performance classes available
- Pressure sensor for reliable pneumatic level measurement
- Maximum operating reliability due to intelligent control unit (Duo)

Description

The lifting station for faecal and faecal-free wastewater is equipped with one or two submersible pumps and a backflow preventer. The collection tank made of permanently resistant polymer (PE) offers universal connection options and has a screwed access cover.

Variant

Type of system: duo pump
Shut-off valve: without shut-off valve
Pressure pipe connection: vertical

General characteristics

Colour: black
Standard: EN 12050-1
Type of wastewater: with sewage
Installation situation: free-standing installation
System type: Duo

Dimensions

Net weight: 198 kg
Gross weight: 218 kg
Packaging dimension: length
Packaging dimension: width
Packaging dimension: height

Tank/drain body

Tank volume: 300 l

Pumping device

Pump: SPF 5500-S3

| | |
|--|-------------------------------|
| Number of pumps: | 2 |
| Weight, pump: | 38 kg |
| Connection type: | Direct connection |
| Protection class: | I |
| Insulation class: | F |
| Protection class (pump): | IP 68 (3m/48h) |
| Temperature monitoring: | integrated |
| Max. temperature (permanent) of conveyed material: | 40 °C |
| Max. pumping capacity: | 60 m ³ /h |
| Max. pumping height: | 28 m |
| Speed: | 2800 U/min |
| Power P1: | 5,7 kW |
| Power P2: | 4,8 kW |
| Operating mode: | S3 - 30 % |
| Type of pump connection cable: | H07RN8-F 6G 1 mm ² |
| Impeller type: | Multi-vane impeller |
| Free passage: | 40 mm |
| Length of mains cable for pump: | 5 m |
| Rated current: | 9,1 A |

| Control | Comfort |
|--------------------------------|-------------------|
| Control unit: | yes |
| Motor protection switch: | Immersion pipe |
| Alarm sensor: | Immersion pipe |
| Level measurement instrument: | pneumatic |
| Type of level measurement: | IP 54 |
| Protection class control unit: | 50 Hz |
| Mains frequency: | 400 V |
| Operating voltage: | Direct connection |
| Connection type: | yes |
| Potential-free contact: | yes |
| GSM interface: | yes |
| Log book function: | yes |
| Multi-line display: | yes |
| Battery buffering: | yes |
| Self-diagnosis system (SDS): | yes |