

## Aqualift F XL, 200 L lift. stat. Duo, SPF 3000-S1, Backflow preventer



## **Article information**

Item no.: 11107

GTIN: 4026092057742

Price group: 50

## **Advantages**

- Different performance classes available
- Pressure sensor for reliable pneumatic level measurement
- Maximum operating reliability due to intelligent control unit (Duo)

## **Description**

The lifting station for faecal and faecal-free wastewater is equipped with one or two submersible pumps and a backflow preventer. The collection tank made of permanently resistant polymer (PE) offers universal connection options and has a screwed access cover.

Variant

Type of system: duo pump
Backflow preventer: integrated
Pressure pipe connection: vertical

General characteristics

Colour: black
Standard: EN 12050-1
Type of wastewater: with sewage

Installation situation: free-standing installation

System type: Duo

**Dimensions** 

Net weight: 174,91 kg
Gross weight: 194,91 kg
Packaging dimension: length
Packaging dimension: width
Packaging dimension: height

Tank/drain body

Tank volume: 200 l

Pumping device

Pump: SPF 3000-S1



Number of pumps: 2 Operating mode: S1

Impeller type: Multi-vane impeller

Free passage: 40 mm Length of mains cable for pump: 5 m

Control

Control unit: Comfort

Level measurement instrument: Immersion pipe
Type of level measurement: pneumatic
Mains frequency: 50 Hz
Operating voltage: 400 V