

Lifting stati. Aqualift F XL 300l Duo, SPF 4500-S1



Article information

Item no.: 11123

GTIN: 4026092057902

Price group: 50

Advantages

- Different performance classes available
- Pressure sensor for reliable pneumatic level measurement
- Maximum operating reliability due to intelligent control unit (Duo)

Description

The lifting station for faecal and faecal-free wastewater is equipped with one or two submersible pumps and a backflow preventer. The collection tank made of permanently resistant polymer (PE) offers universal connection options and has a screwed access cover.

Variant

Type of system: duo pump Pressure pipe connection: vertical

General characteristics

Colour: black
Standard: EN 12050-1
Type of wastewater: with sewage

Installation situation: free-standing installation

System type: Duo

Dimensions

Net weight:200 kgGross weight:220 kgPackaging dimension:lengthPackaging dimension:widthPackaging dimension:height

Tank/drain body

Tank volume: 300 l

Pumping device

Pump: SPF 4500-S1

Number of pumps: 2



Operating voltage: 400 V Operating mode: S1

Impeller type: Multi-vane impeller

Free passage: 40 mm Length of mains cable for pump: 5 m

Control

Control unit: Comfort

Level measurement instrument: Immersion pipe Type of level measurement: pneumatic Mains frequency: $50 \, \text{Hz}$ Operating voltage: $400 \, \text{V}$ Type of fuse required (control unit): $3 \, \text{x} \, \text{C} \, 25 \, \text{A}$