

Lifting stati. Aqualift F XL 300l Duo, SPF 4500-S1



Article information

Item no.: 11123
 GTIN: 4026092057902
 Price group: 50

Advantages

- Different performance classes available
- Pressure sensor for reliable pneumatic level measurement
- Maximum operating reliability due to intelligent control unit (Duo)

Description

The lifting station for faecal and faecal-free wastewater is equipped with one or two submersible pumps and a backflow preventer. The collection tank made of permanently resistant polymer (PE) offers universal connection options and has a screwed access cover.

Variant

Type of system: duo pump
 Pressure pipe connection: vertical

General characteristics

Colour: black
 Standard: EN 12050-1
 Type of wastewater: with sewage
 Installation situation: free-standing installation
 System type: Duo

Dimensions

Net weight: 200 kg
 Gross weight: 220 kg
 Packaging dimension: length
 Packaging dimension: width
 Packaging dimension: height

Tank/drain body

Tank volume: 300 l

Pumping device

Pump: SPF 4500-S1
 Number of pumps: 2

Operating voltage:	400 V
Operating mode:	S1
Impeller type:	Multi-vane impeller
Free passage:	40 mm
Length of mains cable for pump:	5 m
Control	
Control unit:	Comfort
Level measurement instrument:	Immersion pipe
Type of level measurement:	pneumatic
Mains frequency:	50 Hz
Operating voltage:	400 V
Type of fuse required (control unit):	3 x C 25 A