

## Aqualift F XL, 200 L lift. stat. Duo, SPF 1500-S1, shut-off valve



## **Article information**

Item no.: 11133

GTIN: 4026092071175 Price group: 50

## **Advantages**

- Different performance classes available
- Pressure sensor for reliable pneumatic level measurement
- Maximum operating reliability due to intelligent control unit (Duo)

## **Description**

The lifting station for faecal and faecal-free wastewater is equipped with one or two submersible pumps and a backflow preventer. The collection tank made of permanently resistant polymer (PE) offers universal connection options and has a screwed access cover.

Variant

Type of system: duo pump

Shut-off valve: Shut-off valve made of polymer

Backflow preventer: integrated Pressure pipe connection: horizontal

General characteristics

Colour: black

Standard: EN 12050-1 Type of wastewater: with sewage

Installation situation: free-standing installation

System type: Duo

**Dimensions** 

Packaging dimension: length Packaging dimension: width Packaging dimension: height

Tank/drain body

Tank volume: 200 l

Pumping device

Pump: SPF 1500-S1

Number of pumps: 2



Operating mode: S1

Impeller type: Multi-vane impeller

Free passage: 40 mm Length of mains cable for pump: 5 m

Control

Control unit: Comfort

Level measurement instrument: Immersion pipe
Type of level measurement: pneumatic
Mains frequency: 50 Hz
Operating voltage: 400 V