

Technology kit for Ecolift and Pumpfix F



Article information

Item no.: 20000-TK
 GTIN: 4026092097151
 Price group: 30

Description

Technology kit for Ecolift and Pumpfix

Consisting of control unit, pump, motor and 2 optical probes.

Cable length: 5 m

Dimensions

Net weight:	15 kg
Gross weight:	15,45 kg
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height

Pumping device

Pump:	SPZ 1000
Number of pumps:	1
Weight, pump:	10 kg
Connection type:	coded plug
Operating voltage:	230 V
Protection class:	I
Insulation class:	F
Cos phi - power factor:	0,97
Protection class (pump):	IP 68 (3m/48h)
Temperature monitoring:	integrated
Max. temperature (permanent) of conveyed material:	40 °C
Max. pumping capacity:	11,5 m ³ /h
Max. pumping height:	10 m
Speed:	2800 U/min
Power P1:	1,2 kW
Power P2:	0,69 kW
Operating mode:	S3 - 50 %

Type of pump connection cable: H07RN-F 3G 1.5 mm²
Impeller type: Macerator
Length of mains cable for pump: 5 m
Rated current: 5,2 A

Control
Control unit: Comfort
Standby power: 5 W
Alarm sensor: optical probe
Level measurement instrument: optical probe
Type of level measurement: optical
Protection class control unit: IP 54
Operating voltage: 230 V
Connection type: coded plug
Length of mains cable for control unit: 1,4 m
Potential-free contact: yes
GSM interface: no
USB interface: no
Log book function: yes
Multi-line display: yes
Battery buffering: yes
Self-diagnosis system (SDS): yes
Type of fuse required (control unit): C 16 A