


Shell Kit for Minilift L, Floor slab, black cover





Article information

Item no.: 280570S-RBK GTIN: 4026092106839

Price group: 20

Description

For combination with a KESSEL technology kit for creating a Minilift S small lifting station for wastewater without sewage.

The ready to plug in small lifting station for wastewater without sewage is suitable for the disposal of wastewater from individual drainage sources. The submersible pump with float switch can be removed easily with the help of one-handed closures. The collection tank made of polymer (PE) has an open pump tank and is resistant to aggressive wastewater. The system for installation in the floor slab is pre-assembled for final installation on site.

KESSEL shell kit consisting of:

- With vertically adjustable upper section for continuous height and level compensation and integrated floor drain
- Includes backflow preventer for the pressure pipe
- Includes DN 50 connection socket for inlet and conduit pipe

General characteristics

Colour: grey

Standard: EN 12050-2
Type of wastewater: without sewage
Installation situation: floor slab installation

Dimensions

Net weight: 7,61 kg



Gross weight: 7,61 kg

Installation depth: 330 - 460 mm

Length:460 mmWidth:380 mmPackaging dimension:lengthPackaging dimension:widthPackaging dimension:height

Tank/drain body

Pressure pipe connection (DN): 32
Pressure pipe connection (OD): 40 mm
Inlet nominal size (OD): 60 mm
Inlet nominal size (DN): 50 mm
Pumping volume: 7 l

Coverage features

Type of cover: Cover plate with slotted cover

Cover material:

Colour of cover:

Width of cover:

Length of cover:

Locking:

Lock & Lift

Load class:

Rolymer

black

366 mm

Lock & Lift

K 3 (EN 1253-1)