


Shell Kit for Minilift L, Floor slab, black cover





Article information

Item no.: 280570S-RBK GTIN: 4026092106839 Price group: 20

Description

For combination with a KESSEL technology kit for creating a Minilift S small lifting station for wastewater without sewage.

The ready to plug in small lifting station for wastewater without sewage is suitable for the disposal of wastewater from individual drainage sources. The submersible pump with float switch can be removed easily with the help of one-handed closures. The collection tank made of polymer (PE) has an open pump tank and is resistant to aggressive wastewater. The system for installation in the floor slab is pre-assembled for final installation on site.

KESSEL shell kit consisting of:

- With vertically adjustable upper section for continuous height and level compensation and integrated floor drain

- Includes backflow preventer for the pressure pipe

- Includes DN 50 connection socket for inlet and conduit pipe

General characteristics Colour: Standard: Type of wastewater: Installation situation:

grey EN 12050-2 without sewage floor slab installation

Dimensions Net weight:

7,61 kg



Gross weight: Installation depth: Length: Width: Packaging dimension: Packaging dimension: Packaging dimension:

Tank/drain body Pressure pipe connection (DN): Pressure pipe connection (OD): Inlet nominal size (OD): Inlet nominal size (DN): Pumping volume:

Coverage features Type of cover: Cover material: Colour of cover: Width of cover: Length of cover: Locking: Load class: 7,61 kg 330 - 460 mm 460 mm 380 mm length width height

32 40 mm 60 mm 50 mm 7 l

Cover plate with slotted cover Polymer black 366 mm 366 mm Lock & Lift K 3 (EN 1253-1)