


Lifting station Minilift L KTP 300-S1, Floor slab, black





Article information

Item no.: 280570S GTIN: 4026092082553

Price group: 20

Advantages

- Space-saving installation in the floor slab with integrated drainage function
- System ready to plug in
- Easy tool-free maintenance

Description

The ready to plug in small lifting station for faecal-free wastewater is suitable for wastewater drainage of individual sanitary appliances. The submersible pump with float switch can be removed easily with the help of one-handed closures. The collection tank made of polymer (PE) has an open pump tank and is resistant to aggressive wastewater. The system for installation in the floor slab is preassembled for final installation on site.

Variant

Type of system: Single unit Pump control: Float switch Backflow preventer: integrated

General characteristics

Colour: grey

Standard: EN 12050-2
Type of wastewater: without sewage
Installation situation: floor slab installation

Delivery state: Installation-ready (connection parts must be

connected on site)

Dimensions

Net weight: 10,97 kg Gross weight: 12,1 kg

Installation depth: 330 - 460 mm



Length:460 mmWidth:380 mmPackaging dimension:lengthPackaging dimension:widthPackaging dimension:height

Tank/drain body

Pressure pipe connection (DN): 32
Pressure pipe connection (OD): 40 mm
Inlet nominal size (OD): 60 mm
Inlet nominal size (DN): 50 mm
Pumping volume: 7 l

Coverage features

Type of cover: Cover plate with slotted cover

Cover material:

Colour of cover:

Width of cover:

Length of cover:

Locking:

Lock & Lift

Load class:

Polymer

black

366 mm

Lock & Lift

K 3 (EN 1253-1)

Pumping device

Pump: KTP 300

Number of pumps: 1

Connection type: Schuko (earthed contact) 2-pin

Operating voltage: 230 V
Protection class (pump): IP 68 (3m)
Temperature monitoring: integrated
Max. temperature (permanent) of conveyed 40 °C

material:

Hot water resistance for a short time (2 min): $80 \, ^{\circ}\text{C}$ Max. pumping capacity: $8 \, \text{m}^{3}/\text{h}$ Max. pumping height: $6 \, \text{m}$

 Speed:
 2800 U/min

 Power P1:
 0,34 kW

 Power P2:
 0,21 kW

 Operating mode:
 S1

Type of pump connection cable: H07RN-F 3G 1.5 mm² Impeller type: Multi-vane impeller

Free passage: 10 mm
Type of fuse required (pump): C 16 A
Length of mains cable for pump: 5 m
Rated current: 1,6 A

Control

Mains frequency: 50 Hz Operating voltage: 230 V

Connection type: Schuko (earthed contact) 2-pin