


Aquadive GTF 500 submersible pump with float switch, 10 m



Article information

Item no.: 280810
 GTIN: 4026092082515
 Price group: 20

Advantages

- Multi-vane vortex impeller for maximum reliability
- Longitudinally watertight potted connection cable
- Integrated shallow extraction

Description

Submersible pump GTF 500 for faecal-free wastewater

- housing made of polymer/stainless steel
- with longitudinally watertight, moulded connection cable
- with float switch for level measurement
- with removable intake cage and carry handle
- with vertical pressure pipe connection
- with multi-vane impeller for maximum operating reliability
- with integrated low-level suction

Variant

Pump control:	Float switch
Pressure pipe connection:	vertical

General characteristics

Material:	Polymer
Standard:	EN 12050-2
Type of wastewater:	without sewage
Cable length:	10 m

Dimensions

Net weight:	6,09 kg
Gross weight:	6,97 kg

Length:	185 mm
Width:	120 mm
Height:	220 mm
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height
Pumping device	
Pump:	GTF 500
Number of pumps:	1
Weight, pump:	6 kg
Connection type:	Schuko (earthed contact) 2-pin
Operating voltage:	230 V
Protection class:	I
Insulation class:	F
Cos phi - power factor:	0,91
Protection class (pump):	IP 68 (3m)
Temperature monitoring:	integrated
Max. temperature (permanent) of conveyed material:	40 °C
Hot water resistance for a short time (2 min):	80 °C
Max. pumping height:	8 m
Speed:	2800 U/min
Power P1:	0,5 kW
Power P2:	0,36 kW
Operating mode:	S1
Type of pump connection cable:	H07RN-F 3G 1.5 mm ²
Impeller type:	Multi-vane impeller
Free passage:	10 mm
Type of fuse required (pump):	C 16 A
Length of mains cable for pump:	10 m
Rated current:	2,5 A
Control	
Type of level measurement:	mechanical
Mains frequency:	50 Hz
Operating voltage:	230 V
Connection type:	Schuko (earthed contact) 2-pin