


## Aqualift S Compact lift stat. Duo, GTF 1200 resist., Floor slab





## Article information

Item no.: 281230SC GTIN: 4026092093740

Price group: 20

## **Advantages**

- Space-saving due to installation in floor slab with integrated drainage function
- Easy retrofitting from Mono to Duo possible
- Quiet operation, as the pump installation does not cause any structure-borne sound emissions.

## **Description**

The ready to plug in lifting station for faecal-free wastewater is equipped with one or two submersible pumps and a backflow preventer. The collection tank made of permanently resistant polymer (PE) has an open pump tank. One-handed closures enable easy removal of the integrated components. The system for installation in the floor slab is preassembled for final installation on site.

Variant

Type of system: duo pump

Resistant:

and condensate

Pump control: Backflow preventer:

General characteristics

Colour:

Standard:

Type of wastewater: Installation situation:

Delivery state:

System type:

Resistant to waste water containing salt, softener

Control unit

integrated

black

EN 12050-2

without sewage

floor slab installation

Installation-ready (connection parts must be

connected on site)

Duo



**Dimensions** 

Net weight: 22,8 kg
Gross weight: 24,3 kg
Groundwater resistant from lower edge of base 3000 mm

section:

Installation depth: 490 - 620 mm

Type of height adjustability: vertically adjustable upper section

Length: 617 mm
Width: 585 mm
Packaging dimension: length
Packaging dimension: width
Packaging dimension: height

Tank/drain body

Pressure pipe connection (DN): 32
Pressure pipe connection (OD): 40 mm
Inlet nominal size (DN): 100 mm
Pumping volume: 20 l
Tank volume: 65 l

Coverage features

Type of cover:

Cover material:

Colour of cover:

Width of cover:

Length of cover:

Drainage function:

Cover plate

Polymer

black

366 mm

366 mm

yes

Locking: Lock & Lift
Load class: K 3 (EN 1253-1)

Pumping device

Pump: GTF 1200 resistant

Number of pumps: 2
Weight, pump: 10 kg
Connection type: coded plug

Protection class: I Insulation class: F

Protection class (pump): IP 68 (3m) Max. temperature (permanent) of conveyed  $40 \,^{\circ}\text{C}$ 

material:

Hot water resistance for a short time (2 min):  $80 \, ^{\circ}\text{C}$  Max. pumping capacity:  $15,5 \, \text{m}^3/\text{h}$  Max. pumping height:  $9 \, \text{m}$ 

Speed: 2650 U/min
Power P1: 1,4 kW
Power P2: 0,84 kW
Operating mode: S1

Type of pump connection cable: H07RN-F 3G 1.5 mm²
Impeller type: Multi-vane impeller

Free passage: 30 mm



Length of mains cable for pump: 5 m Rated current: 6,2 A

Control

Control unit: Comfort

Control unit function: With alarm message

Motor protection switch: ves

Alarm sensor: optical probe Level measurement instrument: Immersion pipe pneumatic Type of level measurement: Protection class control unit: IP 54 Mains frequency: 50 Hz Operating voltage: 230 V Connection type: coded plug Length of mains cable for control unit: 1.4 m optional yes yes

Potential-free contact: GSM interface: USB interface: Log book function: yes Multi-line display: yes Battery buffering: yes Self-diagnosis system (SDS): yes

Warning equipment version: acoustic and optical signal

Type of fuse required (control unit): C 16 A