

Replacement pump KTP/SPZ 1000 230 V, with float switch



Article information

Item no.: 28301
 GTIN: 4026092038413
 Price group: 90

Description

Replacement pump with macerator and float switch incl. Bracket for wastewater with sewage

Variant

Pump control: Float switch

General characteristics

Standard: EN 12050-1
 Type of wastewater: with sewage

Dimensions

Net weight: 10,47 kg
 Gross weight: 10,8 kg
 Packaging dimension: length
 Packaging dimension: width
 Packaging dimension: height

Pumping device

Pump: SPZ 1000
 Connection type: Schuko (earthed contact) 2-pin
 Operating voltage: 230 V
 Mains frequency: 50 Hz
 Protection class: I
 Insulation class: F
 Cos phi - power factor: 0,97
 Protection class (pump): IP 68 (3m/48h)
 Temperature monitoring: integrated
 Max. temperature (permanent) of conveyed material: 35 °C
 Max. pumping height: 10 m
 Speed: 2800 U/min
 Power P1: 1,2 kW
 Power P2: 0,7 kW

Operating mode:	S3 - 50 %
Type of pump connection cable:	H07RN-F 3G 1.5 mm ²
Type of fuse required (pump):	C 16 A
Length of mains cable for pump:	5 m
Rated current:	5,2 A
Control	
Operating voltage:	230 V
Connection type:	Schuko (earthed contact) 2-pin