

Replacement pump KTP/SPZ 1000 230 V, cable length 5 m



Article information

Item no.: 28351
GTIN: 4026092038420
Price group: 90

Description

Replacement pump with macerator for wastewater with sewage

Variant

Pump control: Control unit

General characteristics

Standard: EN 12050-1
Type of wastewater: with sewage

Dimensions

Net weight: 10,29 kg
Gross weight: 10,62 kg
Packaging dimension: length
Packaging dimension: width
Packaging dimension: height

Pumping device

Pump: SPZ 1000
Connection type: coded plug
Operating voltage: 230 V
Mains frequency: 50 Hz
Protection class: I
Insulation class: F
Cos phi - power factor: 0,97
Protection class (pump): IP 68 (3m/48h)
Temperature monitoring: integrated
Max. temperature (permanent) of conveyed material: 35 °C
Max. pumping height: 10 m
Speed: 2800 U/min
Power P1: 1,2 kW
Power P2: 0,7 kW
Operating mode: S3 - 50 %

Type of pump connection cable:	H07RN-F 3G 1.5 mm ²
Impeller type:	Macerator
Type of fuse required (pump):	Fuse protection through control unit 230 V
Length of mains cable for pump:	5 m
Rated current:	5,2 A
Control	
Operating voltage:	230 V
Connection type:	coded plug