

Replacement pump KTP/SPZ 1000 230 V, with extended press. pipe connec.



Article information

Item no.: 28739

GTIN: 4026092051979

Price group: 90

Description

Replacement pump with extended pressure pipe connection and macerator for wastewater with sewage, ready for connection with coded plug

General characteristics

| | |
|---------------------|-------------|
| Standard: | EN 12050-1 |
| Type of wastewater: | with sewage |

Dimensions

| | |
|----------------------|----------|
| Net weight: | 9,67 kg |
| Gross weight: | 10,37 kg |
| Packaging dimension: | length |
| Packaging dimension: | width |
| Packaging dimension: | height |

Pumping device

| | |
|--|----------------|
| Pump: | SPZ 1000 |
| Connection type: | coded plug |
| Operating voltage: | 230 V |
| Mains frequency: | 50 Hz |
| Protection class: | I |
| Insulation class: | F |
| Cos phi - power factor: | 0,97 |
| Protection class (pump): | IP 68 (3m/48h) |
| Temperature monitoring: | integrated |
| Max. temperature (permanent) of conveyed material: | 35 °C |
| Max. pumping height: | 10 m |
| Speed: | 2800 U/min |
| Power P1: | 1,2 kW |
| Power P2: | 0,7 kW |
| Operating mode: | S3 - 50 % |

| | |
|---------------------------------|--------------------------------|
| Type of pump connection cable: | H07RN-F 3G 1.5 mm ² |
| Impeller type: | Macerator |
| Length of mains cable for pump: | 5 m |
| Rated current: | 5,2 A |

| | |
|--|------------|
| Control | |
| Operating voltage: | 230 V |
| Connection type: | coded plug |
| Type of fuse required (electrical protection): | C 16 A |