

Comfort control unit 400V, Aqualift Mono, 2.5-4.0 A



Article information

Item no.: 28755

GTIN: 4026092055007

Price group: 20

Advantages

- Self-diagnosis system (SDS)
- Potential-free contact for faults/warnings
- Reminder for when maintenance is due

Description

Komfort control unit for lifting stations or pumping stations. Suitable for 400 V single stations. Optional connection option for float switches, conductivity probes and level probe on the terminal strip. User-friendly menu navigation in multi-line display. Menu navigation in six languages. Simple selection of the system to be connected with preset, system-specific operating parameters. Display of the current measured values. Simple adjustment of the function-related parameters, with integrated operating hour counter. With self-diagnosis system (SDS) for monitoring pump, sensors and battery back-up. Improper installation or operating faults trigger an optical and acoustic alarm signal. Forwarding of a collective fault and alarm signals via optional potential-free contact or integrated serial interface for GSM modem.

Variant

Series: ab 03/2010 Type of system: Single unit

General characteristics

Colour: grey System type: Mono

Dimensions

Net weight:2,47 kgGross weight:3,19 kgPackaging dimension:lengthPackaging dimension:widthPackaging dimension:height

Control

Control unit: Comfort

Motor protection switch: yes

Protection class control unit: IP 54



Operating voltage: 400 V Potential-free contact: yes GSM interface: yes USB interface: no Log book function: yes Multi-line display: yes Battery buffering: yes Self-diagnosis system (SDS): yes 2,5 - 4 A Rated current: