

Comfort control unit 400V, Aqualift Duo, 2x2.5-4.0 A



Article information

Item no.: 28757

GTIN: 4026092055021

Price group: 20

Advantages

- Self-diagnosis system (SDS)
- Potential-free contact for faults/warnings
- Reminder for when maintenance is due

Description

Comfort control unit for lifting stations or pumping stations. Suitable for 400 V double stations. Optional connection options for float switches, conductivity probes, and level probes on the terminal strip. User-friendly menu navigation on the multi-line display. Menu navigation in six languages. Simple selection of the system to be connected with preset, system-specific operating parameters. Display of current measured values. Simple adjustment of function-relevant parameters, with integrated operating hour counter. With self-diagnosis system (SDS) for monitoring pump, sensors and battery back-up. Improper installation or operating faults trigger an optical and acoustic alarm signal. Forwarding of a collective fault and alarm signal via optional potential-free contact or integrated serial interface for a GSM modem.

Variant

Series: ab 03/2010 Type of system: duo pump

General characteristics

Colour: grey System type: Duo

Dimensions

Net weight:3,17 kgGross weight:3,83 kgPackaging dimension:lengthPackaging dimension:widthPackaging dimension:height

Control

Control unit: Comfort

Motor protection switch: yes

Protection class control unit: IP 54



Operating voltage: 400 V Potential-free contact: yes GSM interface: yes USB interface: no Log book function: yes Multi-line display: yes Battery buffering: yes Self-diagnosis system (SDS): yes 2,5 - 4 A Rated current: