


Comfort control unit 400V, Aqualift Duo, 2x4.0-6.3 A





Article information

Item no.: 28758

GTIN: 4026092055038

Price group: 20

Advantages

- Self-diagnosis system (SDS)
- Potential-free contact for faults/warnings
- Reminder for when maintenance is due

Description

Comfort control unit for lifting stations or pumping stations. Suitable for 400 V double stations. Optional connection options for float switches, conductivity probes, and level probes on the terminal strip. User-friendly menu navigation on the multi-line display. Menu navigation in six languages. Simple selection of the system to be connected with preset, system-specific operating parameters. Display of current measured values. Simple adjustment of function-relevant parameters, with integrated operating hour counter. With self-diagnosis system (SDS) for monitoring pump, sensors and battery back-up. Improper installation or operating faults trigger an optical and acoustic alarm signal. Forwarding of a collective fault and alarm signal via optional potential-free contact or integrated serial interface for a GSM modem.

Variant

Series: ab 03/2010 Type of system: duo pump

General characteristics

Colour: grey System type: Duo

Dimensions

Net weight: 3,17 kg
Gross weight: 3,83 kg
Packaging dimension: length
Packaging dimension: width
Packaging dimension: height



Control

Control unit: Comfort Motor protection switch: yes Protection class control unit: IP 54 Potential-free contact: yes GSM interface: yes USB interface: no Log book function: yes Multi-line display: yes Battery buffering: yes Self-diagnosis system (SDS): yes 4 - 6,3 A Rated current: