


Comfort control unit 400V, Aqualift Duo, 2x4.0-6.3 A



Article information

Item no.: 28758
GTIN: 4026092055038
Price group: 20

Advantages

- Self-diagnosis system (SDS)
- Potential-free contact for faults/warnings
- Reminder for when maintenance is due

Description

Comfort control unit for lifting stations or pumping stations. Suitable for 400 V double stations. Optional connection options for float switches, conductivity probes, and level probes on the terminal strip. User-friendly menu navigation on the multi-line display. Menu navigation in six languages. Simple selection of the system to be connected with preset, system-specific operating parameters. Display of current measured values. Simple adjustment of function-relevant parameters, with integrated operating hour counter. With self-diagnosis system (SDS) for monitoring pump, sensors and battery back-up. Improper installation or operating faults trigger an optical and acoustic alarm signal. Forwarding of a collective fault and alarm signal via optional potential-free contact or integrated serial interface for a GSM modem.

Variant

Series:	ab 03/2010
Type of system:	duo pump

General characteristics

Colour:	grey
System type:	Duo

Dimensions

Net weight:	3,17 kg
Gross weight:	3,83 kg
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height

Control

Control unit:

Motor protection switch:

Protection class control unit:

Potential-free contact:

GSM interface:

USB interface:

Log book function:

Multi-line display:

Battery buffering:

Self-diagnosis system (SDS):

Rated current:

Comfort

yes

IP 54

yes

yes

no

yes

yes

yes

yes

4 - 6,3 A