


## Submersible pump Aquadive GTF1000 without float switch, 10m





## **Article information**

Item no.: 28760

GTIN: 4026092044520

Price group: 20

## **Advantages**

- Multi-vane vortex impeller for maximum reliability
- Longitudinally watertight potted connection cable
- Integrated shallow extraction

## Description

Submersible pump for faecal-free wastewater,

type KTP 1000, new designation:

GTF 1000

Variant

Pump control: without float switch

General characteristics

Standard: EN 12050-2 Type of wastewater: without sewage

Dimensions

Net weight: 11,05 kg
Gross weight: 11,38 kg
Length: 195 mm
Packaging dimension: length
Packaging dimension: width
Packaging dimension: height

Pumping device

Pump: GTF 1000
Connection type: coded plug
Operating voltage: 230 V
Protection class:



F Insulation class: 0,97 Cos phi - power factor: Protection class (pump): IP 68 (3m) Temperature monitoring: integrated 35°C

Max. temperature (permanent) of conveyed

material:

Hot water resistance for a short time (2 min): 2°08 Max. pumping height: 10 m

Speed: 2700 U/min Power P1: 1,3 kW Power P2: 0,75 kW Operating mode: S1

Type of pump connection cable: H07RN-F 3G 1.5 mm<sup>2</sup> Impeller type: Multi-vane impeller

Type of fuse required (pump): C 16 A Length of mains cable for pump: 10 m Rated current: 5,6 A

Control

Mains frequency: 50 Hz Operating voltage: 230 V Connection type: coded plug