


## Submersible pump Aquadive GTF1000 without float switch, 10m



### Article information

Item no.: 28760  
 GTIN: 4026092044520  
 Price group: 20

### Advantages

- Multi-vane vortex impeller for maximum reliability
- Longitudinally watertight potted connection cable
- Integrated shallow extraction

### Description

Submersible pump for faecal-free wastewater, type KTP 1000, new designation: GTF 1000

Variant

Pump control: without float switch

General characteristics

Standard: EN 12050-2

Type of wastewater: without sewage

Dimensions

Net weight: 11,05 kg

Gross weight: 11,38 kg

Length: 195 mm

Packaging dimension: length

Packaging dimension: width

Packaging dimension: height

Pumping device

Pump: GTF 1000

Connection type: coded plug

Operating voltage: 230 V

Protection class: I

Insulation class:	F
Cos phi - power factor:	0,97
Protection class (pump):	IP 68 (3m)
Temperature monitoring:	integrated
Max. temperature (permanent) of conveyed material:	35 °C
Hot water resistance for a short time (2 min):	80 °C
Max. pumping height:	10 m
Speed:	2700 U/min
Power P1:	1,3 kW
Power P2:	0,75 kW
Operating mode:	S1
Type of pump connection cable:	H07RN-F 3G 1.5 mm <sup>2</sup>
Impeller type:	Multi-vane impeller
Type of fuse required (pump):	C 16 A
Length of mains cable for pump:	10 m
Rated current:	5,6 A
Control	
Mains frequency:	50 Hz
Operating voltage:	230 V
Connection type:	coded plug