

## Aquadive STZ1000 submersible pump resistant, with float switch, 10 m



## **Article information**

Item no.: 28778

GTIN: 4026092055878

Price group: 20

## **Advantages**

- Multi-vane vortex impeller for maximum reliability
- Longitudinally watertight potted connection cable
- Integrated shallow extraction

## **Description**

Replacement pump Aquadive, with macerator and float control.

Variant

Pump control: Float switch

General characteristics

Material: Polymer
Standard: EN 12050-1
Type of wastewater: with sewage

Cable length: 10 m

**Dimensions** 

Net weight: 11,2 kg Gross weight: 11,53 kg Length: 258 mm Width: 258 mm 294 mm Height: Packaging dimension: length Packaging dimension: width Packaging dimension: height

Pumping device

Protection class:

Pump: STZ 1000
Number of pumps: 1
Weight, pump: 10 kg

Connection type: coded plug
Operating voltage: 230 V



Insulation class: F
Cos phi - power factor: 0,97
Protection class (pump): IP 68 (3m)
Temperature monitoring: integrated
Max. temperature (permanent) of conveyed 40 °C

material:

Hot water resistance for a short time (2 min):  $80 \,^{\circ}\text{C}$  Max. pumping height:  $10 \, \text{m}$ 

 Speed:
 2800 U/min

 Power P1:
 1,2 kW

 Power P2:
 0,69 kW

Operating mode: 0,69 kW S3 - 50 %

Type of pump connection cable: H07RN-F 3G 1.5 mm<sup>2</sup>

Impeller type: Macerator Type of fuse required (pump): C 16 A
Length of mains cable for pump: 10 m
Rated current: 4,9 A

Control

Type of level measurement: mechanical Mains frequency: 50 Hz
Operating voltage: 230 V
Connection type: coded plug