

Aquadive STZ1000 submersible pump resistant, with float switch, 10 m



Article information

Item no.: 28778
GTIN: 4026092055878
Price group: 20

Advantages

- Multi-vane vortex impeller for maximum reliability
- Longitudinally watertight potted connection cable
- Integrated shallow extraction

Description

Replacement pump Aquadive, with macerator and float control.

Variant

Pump control: **Float switch**

General characteristics

Material: **Polymer**
Standard: **EN 12050-1**
Type of wastewater: **with sewage**
Cable length: **10 m**

Dimensions

Net weight: **11,2 kg**
Gross weight: **11,53 kg**
Length: **258 mm**
Width: **258 mm**
Height: **294 mm**
Packaging dimension: **length**
Packaging dimension: **width**
Packaging dimension: **height**

Pumping device

Pump: **STZ 1000**
Number of pumps: **1**
Weight, pump: **10 kg**
Connection type: **coded plug**
Operating voltage: **230 V**
Protection class: **I**

Insulation class:	F
Cos phi - power factor:	0,97
Protection class (pump):	IP 68 (3m)
Temperature monitoring:	integrated
Max. temperature (permanent) of conveyed material:	40 °C
Hot water resistance for a short time (2 min):	80 °C
Max. pumping height:	10 m
Speed:	2800 U/min
Power P1:	1,2 kW
Power P2:	0,69 kW
Operating mode:	S3 - 50 %
Type of pump connection cable:	H07RN-F 3G 1.5 mm ²
Impeller type:	Macerator
Type of fuse required (pump):	C 16 A
Length of mains cable for pump:	10 m
Rated current:	4,9 A

Control

Type of level measurement:	mechanical
Mains frequency:	50 Hz
Operating voltage:	230 V
Connection type:	coded plug