

Submersible pump Aquadive STZ1000 without float switch, 10 m



Article information

Item no.: 28779

GTIN: 4026092055885

Price group: 20

Advantages

- Multi-vane vortex impeller for maximum reliability
- Longitudinally watertight potted connection cable
- Integrated shallow extraction

Description

Replacement pump Aquadive without ATEX, with macerator, without float control.

Variant

Pump control: without float switch

General characteristics

Material: Polymer
Standard: EN 12050-1
Type of wastewater: with sewage

Cable length: 10 m

Dimensions

Net weight: 10,52 kg Gross weight: 11 kg 258 mm Length: Width: 258 mm Height: 294 mm Packaging dimension: length Packaging dimension: width Packaging dimension: height

Pumping device

Pump: STZ 1000

Number of pumps:

Weight, pump:

Connection type:

Operating voltage:

Protection class:

Insulation class:

1

10 kg

coded plug

230 V

F



Cos phi - power factor: 0,97
Protection class (pump): IP 68 (3m)
Temperature monitoring: integrated
Max. temperature (permanent) of conveyed 40 °C

material:

Hot water resistance for a short time (2 min): 80 °C Max. pumping height: 10 m

 Speed:
 2800 U/min

 Power P1:
 1,2 kW

 Power P2:
 0,69 kW

 Operating mode:
 \$3 - 30 %

Type of pump connection cable: H07RN-F 3G 1.5 mm²

Impeller type: Macerator Type of fuse required (pump): C 16 A Length of mains cable for pump: 10 m Rated current: 4,9 A

Control

Mains frequency:50 HzOperating voltage:230 VConnection type:coded plug