

## Replacement pump KTP 300 for Minilift



### Article information

Item no.: 28836  
 GTIN: 4026092000922  
 Price group: 90

### Description

Replacement pump for sewage-free wastewater

Variant

Pump control: Float switch

General characteristics

Standard: EN 12050-2  
 Type of wastewater: without sewage  
 Cable length: 5 m

Dimensions

Net weight: 4,21 kg  
 Gross weight: 4,49 kg  
 Packaging dimension: length  
 Packaging dimension: width  
 Packaging dimension: height

Pumping device

Pump: KTP 300  
 Connection type: Schuko (earthed contact) 2-pin  
 Operating voltage: 230 V  
 Mains frequency: 50 Hz  
 Protection class: I  
 Insulation class: F  
 Protection class (pump): IP 68 (3m)  
 Temperature monitoring: integrated  
 Max. temperature (permanent) of conveyed material: 35 °C  
 Max. pumping height: 6 m  
 Speed: 2800 U/min  
 Power P1: 0,34 kW  
 Power P2: 0,21 kW  
 Operating mode: S1

Type of pump connection cable:	H07RN-F 3G 1.5 mm <sup>2</sup>
Length of mains cable for pump:	5 m
Rated current:	1,9 A
Control	
Operating voltage:	230 V
Connection type:	Schuko (earthed contact) 2-pin
Type of fuse required (electrical protection):	C 16 A