

Submersible pump Aquadive KTP 300 with float switch, 10m

Article information



Item no.: 28840
GTIN: 4026092000939
Price group: 20

Advantages

- Multi-vane vortex impeller for maximum reliability
- Longitudinally watertight potted connection cable
- Integrated shallow extraction

Description

KTP 300 submersible pump with float switch, with non-return flap, pivoted connection, removable intake cage; the water level can be lowered to 8 mm.

Variant

Pump control: **Float switch**

General characteristics

Material: **Polymer**
Standard: **EN 12050-2**
Type of wastewater: **without sewage**
Cable length: **10 m**

Dimensions

Net weight: **4,61 kg**
Gross weight: **4,89 kg**
Length: **275 mm**
Width: **390 mm**
Height: **216 mm**
Packaging dimension: length
Packaging dimension: width
Packaging dimension: height

Pumping device

Pump: **KTP 300**
Number of pumps: **1**
Weight, pump: **4 kg**
Connection type: **Schuko (earthed contact) 2-pin**

Operating voltage:	230 V
Protection class:	I
Insulation class:	F
Protection class (pump):	IP 68 (3m)
Temperature monitoring:	integrated
Max. temperature (permanent) of conveyed material:	40 °C
Hot water resistance for a short time (2 min):	80 °C
Max. pumping height:	6 m
Speed:	2800 U/min
Power P1:	0,34 kW
Power P2:	0,21 kW
Operating mode:	S1
Type of pump connection cable:	H07RN-F 3G 1.5 mm ²
Impeller type:	Multi-vane impeller
Free passage:	10 mm
Type of fuse required (pump):	C 16 A
Length of mains cable for pump:	10 m
Rated current:	1,6 A

Control

Type of level measurement:	mechanical
Mains frequency:	50 Hz
Operating voltage:	230 V
Connection type:	Schuko (earthed contact) 2-pin