

Submersible pump Aquadive KTP 300 with float switch, 10m



Article information

Item no.: 28840

GTIN: 4026092000939

Price group: 20

Advantages

- Multi-vane vortex impeller for maximum reliability
- Longitudinally watertight potted connection cable
- Integrated shallow extraction

Description

KTP 300 submersible pump with float switch, with non-return flap, pivoted connection, removable intake cage; the water level can be lowered to 8 mm.

Variant

Pump control: Float switch

General characteristics

Material: Polymer
Standard: EN 12050-2
Type of wastewater: without sewage

Cable length: 10 m

Dimensions

Net weight: 4,61 kg Gross weight: 4,89 kg Length: 275 mm Width: 390 mm Height: 216 mm Packaging dimension: length Packaging dimension: width Packaging dimension: height

Pumping device

Pump: KTP 300 Number of pumps: 1

Weight, pump: 4 kg

Connection type: Schuko (earthed contact) 2-pin



Operating voltage: 230 V Protection class: I Insulation class: F

Protection class (pump): IP 68 (3m) Temperature monitoring: integrated Max. temperature (permanent) of conveyed $40\,^{\circ}\text{C}$

material:

Hot water resistance for a short time (2 min): 80 °C Max. pumping height: 6 m

Speed: 2800 U/min Power P1: 0,34 kW Power P2: 0,21 kW Operating mode: S1

Type of pump connection cable: H07RN-F 3G 1.5 mm² Impeller type: Multi-vane impeller

Free passage: 10 mm
Type of fuse required (pump): C 16 A
Length of mains cable for pump: 10 m
Rated current: 1,6 A

Control

Type of level measurement: mechanical Mains frequency: 50 Hz
Operating voltage: 230 V

Connection type: Schuko (earthed contact) 2-pin