


Aquadive KTP 300 submersible pump resistant, with float switch, 10 m





Article information

Item no.: 28840C GTIN: 4026092093634

Price group: 20

Advantages

- Multi-vane vortex impeller for maximum reliability
- Longitudinally watertight potted connection cable
- Integrated shallow extraction

Description

KTP 300 submersible pump with float switch, with non-return flap, pivoted connection, removable intake cage; the water level can be lowered to 8 mm.

Variant

Resistant: Resistant to waste water containing salt, softener

and condensate

Pump control: Float switch Backflow preventer: integrated

General characteristics

Type of wastewater: without sewage

Cable length: 10 m

Dimensions

Net weight:4,45 kgGross weight:4,81 kgLength:275 mmWidth:390 mmHeight:216 mmPackaging dimension:lengthPackaging dimension:width



Packaging dimension: height

Pumping device

Pump: KTP 300 resistant

Number of pumps: 1
Weight, pump: 4 kg

Connection type: Schuko (earthed contact) 2-pin

Operating voltage: 230 V
Protection class: I
Insulation class: F
Protection class (pump): IP 68
Max. temperature (permanent) of conveyed 40 °C

material:

Hot water resistance for a short time (2 min): 80 °C Max. pumping height: 6 m

 Speed:
 2800 U/min

 Power P1:
 0,34 kW

 Power P2:
 0,21 kW

 Operating mode:
 S1

Type of pump connection cable: H07RN-F 3G 1.5 mm² Impeller type: Multi-vane impeller

Free passage: 10 mm
Type of fuse required (pump): C 16 A
Length of mains cable for pump: 10 m
Rated current: 1,9 A

Control

Type of level measurement: mechanical Mains frequency: 50 Hz
Operating voltage: 230 V

Connection type: Schuko (earthed contact) 2-pin