


## Submersible pump Aquadive GTF1000 with float switch, 10m



### Article information

Item no.: 28860  
 GTIN: 4026092044513  
 Price group: 20

### Advantages

- Multi-vane vortex impeller for maximum reliability
- Longitudinally watertight potted connection cable
- Integrated shallow extraction

### Description

Submersible pump for faecal-free wastewater, type KTP 1000, new designation:

GTF 1000

Variant

Pump control:

Float switch

General characteristics

Material:

Polymer

Standard:

EN 12050-2

Type of wastewater:

without sewage

Cable length:

10 m

Dimensions

Net weight:

10 kg

Gross weight:

11,19 kg

Length:

195 mm

Width:

195 mm

Height:

290 mm

Packaging dimension:

length

Packaging dimension:

width

Packaging dimension:

height

Pumping device

Pump:	GTF 1000
Number of pumps:	1
Weight, pump:	10 kg
Connection type:	coded plug
Operating voltage:	230 V
Protection class:	I
Insulation class:	F
Cos phi - power factor:	0,97
Protection class (pump):	IP 68 (3m)
Temperature monitoring:	integrated
Max. temperature (permanent) of conveyed material:	40 °C
Hot water resistance for a short time (2 min):	80 °C
Max. pumping height:	10 m
Speed:	2700 U/min
Power P1:	1,3 kW
Power P2:	0,75 kW
Operating mode:	S3 - 50 %
Type of pump connection cable:	H07RN-F 3G 1.5 mm <sup>2</sup>
Impeller type:	Multi-vane impeller
Free passage:	10 mm
Type of fuse required (pump):	C 16 A
Length of mains cable for pump:	10 m
Rated current:	5,6 A
Control	
Type of level measurement:	mechanical
Mains frequency:	50 Hz
Operating voltage:	230 V
Connection type:	coded plug