


## Submersible pump Aquadive GTF1000 resistant, with float switch, 10 m





## **Article information**

Item no.: 28860C GTIN: 4026092093771

Price group: 20

## **Advantages**

- Multi-vane vortex impeller for maximum reliability
- Longitudinally watertight potted connection cable
- Integrated shallow extraction

## **Description**

Submersible pump for faecal-free wastewater

Variant

Resistant: Resistant to waste water containing salt, softener

and condensate

Pump control: Float switch

General characteristics

Type of wastewater: without sewage

**Dimensions** 

Net weight: 10 kg Gross weight: 10,5 kg Length: 195 mm Width: 195 mm 290 mm Height: Packaging dimension: length Packaging dimension: width Packaging dimension: height

Pumping device



Pump: GTF 1000 resistant

Weight, pump: 10 kg
Connection type: coded plug
Operating voltage: 230 V
Protection class: I
Insulation class: F

Protection class (pump): IP 68 (3m) Max. temperature (permanent) of conveyed  $40\,^{\circ}\mathrm{C}$ 

material:

Hot water resistance for a short time (2 min):  $80\,^{\circ}\text{C}$  Max. pumping height:  $10\,\text{m}$ 

 Speed:
 2700 U/min

 Power P1:
 1,3 kW

 Power P2:
 0,75 kW

 Operating mode:
 \$3 - 50 %

Type of pump connection cable: H07RN-F 3G 1.5 mm² Impeller type: Multi-vane impeller

Free passage: 10 mm
Type of fuse required (pump): C 16 A
Length of mains cable for pump: 10 m
Rated current: 5,6 A

Control

Type of level measurement: mechanical Mains frequency: 50 Hz Connection type: coded plug