


Universal Plus basement drain ver., odour trap, Waterproof concrete



Article information

Item no.: 29102
 GTIN: 4026092096956
 Price group: 10

Advantages

- Sustainable due to use of recycled material
- Inlets above the floor slab, no penetration required
- Vertical outlet for easy installation and easy access to the main drainage pipe

Description

In combination with an upper section, the polymer Universal Plus drain body is used for drainage of non-faecal wastewater and is equipped with a removable odour trap and a sludge bucket. Including temporary protective cover. The drain is pressure-waterproof up to 0.6 bar (MFPA Leipzig tested) and radon-tight (IAF Radioökologie GmbH tested).

Variant

Contents of sludge trap: yes
 Waterproof flange: Pre-assembled at the factory
 Sealing water height: 60 mm

General characteristics

Colour: black
 Standard: EN 1253
 Nominal size (DN): 100
 Type of wastewater: without sewage
 Installation situation: floor slab installation
 Odour trap: included
 Sustainable: through the use of recycled material

Dimensions

Net weight: 2,38 kg
 Gross weight: 2,79 kg

Diameter:	295 mm
Cutout dimension, width:	310 mm
Cutout dimension, length:	310 mm
Type of height adjustability:	vertically adjustable upper section
Height:	270 mm
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height
Tank/drain body	
Outlet nominal size (OD):	110 mm
Outlet nominal size (DN):	100 mm
Socket version:	vertical
Coverage features	
Contents of sludge trap:	yes