


Universal Plus basement drain vertical, with odour trap





Article information

Item no.: 29103

GTIN: 4026092096963

Price group: 10

Advantages

- Sustainable due to use of recycled material
- Inlets above the floor slab, no penetration required
- Vertical outlet for easy installation and easy access to the main drainage pipe

Description

In combination with an upper section, the polymer Universal Plus drain body is used for drainage of non-faecal wastewater and is equipped with a removable odour trap and a sludge bucket. Including temporary protective cover. The drain is pressure-waterproof up to 0.6 bar (MFPA Leipzig tested) and radon-tight (IAF Radioökologie GmbH tested).

Variant

Contents of sludge trap: yes
Waterproof flange: without
Sealing water height: 60 mm

General characteristics

Colour: black
Standard: EN 1253
Nominal size (DN): 100

Type of wastewater: without sewage Installation situation: floor slab installation

Odour trap: included

Sustainable: through the use of recycled material

Dimensions

Net weight: 1,73 kg Gross weight: 2,22 kg



Diameter: 235 mm
Cutout dimension, width: 310 mm
Cutout dimension, length: 310 mm

Type of height adjustability: vertically adjustable upper section

Height: 270 mm
Packaging dimension: length
Packaging dimension: width
Packaging dimension: height

Tank/drain body

Outlet nominal size (OD): 110 mm
Outlet nominal size (DN): 100 mm
Socket version: vertical

Coverage features

Contents of sludge trap: yes