

## Basement drain DN 100, Black grating, Class K 3



### Article information

Item no.: 29111  
GTIN: 4026092007846  
Price group: 10

### Advantages

- Integrated odour trap
- Including sludge bucket

### Description

The basement drain made of polymer for floor slab installation is equipped with an odour trap and a sludge bucket. The upper section with slotted grating is vertically adjustable.

#### Variant

Contents of sludge trap:	yes
Position of lateral connection:	Type II
Sealing water height:	60 mm
Discharge rate (l/s) with 20 mm threshold:	1,8

#### General characteristics

Standard:	EN 1253-1
Nominal size (DN):	100
Outer diameter (OD):	110 mm
Odour trap:	included

#### Dimensions

Vertical adjustment:	30 - 90 mm
Net weight:	2,55 kg
Gross weight:	2,88 kg
Cutout dimension, width:	320 mm
Cutout dimension, length:	400 mm
Installation depth:	216 - 276 mm
Type of height adjustability:	vertically adjustable upper section
Length:	380 mm
Width:	290 mm
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height

#### Tank/drain body

Inlet nominal size (DN):	70 mm
--------------------------	-------

Number of inlets: 2  
Material of drain body: PP  
Socket version: lateral

**Coverage features**

Type of cover: Slotted cover  
Cover material: Polymer  
Colour of cover: black  
Width of cover: 188 mm  
Length of cover: 188 mm  
Frame material: Polymer  
Locking: placed  
Load class: K 3 (EN 1253-1)  
Rim width: 200 mm  
Rim length: 200 mm  
Upper section material: Polymer  
Contents of sludge trap: yes