

Basement drain DN 100, st st grating, Class L 15



Article information

Item no.: 29121

GTIN: 4026092007853

Price group: 10

Advantages

- Integrated odour trap
- Including sludge bucket

Description

The basement drain made of polymer for floor slab installation is equipped with an odour trap and a sludge bucket. The upper section with slotted grating is vertically adjustable.

Variant

Contents of sludge trap:

Position of lateral connection:

Sealing water height:

Discharge rate (l/s) with 20 mm threshold:

yes

Type II

60 mm

General characteristics

Standard: EN 1253-1
Nominal size (DN): 100
Outer diameter (OD): 110 mm
Odour trap: included

Dimensions

Vertical adjustment:30 - 90 mmNet weight:2,97 kgGross weight:3,3 kgCutout dimension, width:320 mmCutout dimension, length:400 mmInstallation depth:216 - 266 mm

Type of height adjustability: vertically adjustable upper section

Length: 380 mm
Width: 290 mm
Packaging dimension: length
Packaging dimension: width
Packaging dimension: height

Tank/drain body

Inlet nominal size (DN): 70 mm



Number of inlets:2Material of drain body:PPSocket version:lateral

Coverage features

Type of cover: Slotted cover

Cover material: Stainless steel 14301

Colour of cover:blackWidth of cover:187 mmLength of cover:187 mm

Frame material: Stainless steel 14301

Locking: screwed

Load class: K 3 (EN 1253-1)

Rim width: 200 mm
Rim length: 200 mm
Upper section material: Polymer
Contents of sludge trap: yes