


Universal Plus basement drain ver., black, Odour trap, Waterpr. concr.



Article information

Item no.: 29131
 GTIN: 4026092096895
 Price group: 10

Advantages

- Sustainable due to use of recycled material
- Inlets above the floor slab, no penetration required
- Vertical outlet for easy installation and easy access to the main drainage pipe

Description

The polymer Universal Plus basement drain is used for drainage of non-faecal wastewater and is equipped with a removable odour closure. Including temporary protective cover. The drain is pressure-waterproof up to 0.6 bar (MFPA Leipzig tested) and radon-tight (IAF Radioökologie GmbH tested).

Variant

Contents of sludge trap: yes
 Waterproof flange: Pre-assembled at the factory
 Discharge rate (l/s) with 10 mm threshold: 1,4
 Discharge rate (l/s) with 20 mm threshold: 2,5

General characteristics

Colour: black
 Standard: EN 1253
 Nominal size (DN): 100
 Type of wastewater: without sewage
 Installation situation: floor slab installation
 Odour trap: included
 Sustainable: through the use of recycled material

Dimensions

Net weight:	3,17 kg
Gross weight:	3,58 kg
Diameter:	295 mm
Cutout dimension, width:	310 mm
Cutout dimension, length:	310 mm
Adjustment range:	23 - 80
Installation depth:	293 - 350 mm
Type of height adjustability:	vertically adjustable upper section
Height:	270 mm
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height

Tank/drain body

Outlet nominal size (OD):	110 mm
Outlet nominal size (DN):	100 mm
Socket version:	vertical

Coverage features

Type of cover:	Slotted cover
Cover material:	Polymer
Colour of cover:	black
Width of cover:	200 mm
Height of cover:	25 mm
Length of cover:	200 mm
Load class:	K 3 (EN 1253-1)
Contents of sludge trap:	yes