


The Ultraflat 54 floor drain DN40, WaD, Design cover, L&L, Megastop





Article information

Item no.: 44740.66M GTIN: 4026092080818

Price group: 10

Advantages

- including removable odour trap in the upper
- Low installation depth
- Scientifically confirmed sound insulation effect

Description

The Ultraflat 54 floor drain is suitable for indoor floor drainage. The polymer drain is equipped with a removable odour trap in the upper section. Open seepage water opening, no flooding of the waterproofing level in the event of build-up.

Variant

125 System: Seepage opening: optional Backflow protection: up to 0.1 bar

Waterproofing layer on the drain body: Factory-fitted sealing collar (WaD) according to DIN

> 18534 W3-I

Water exposure class in accordance to DIN

18534-1 (up to and including):

Sealing water height: 10 mm

General characteristics

40 Nominal size (DN): Outer diameter (OD): 40 mm Odour trap: Megastop

Sustainable: through the use of recycled material

Dimensions

Vertical adjustment: 70 - 121 mm Net weight: $0,65 \, \text{kg}$ Gross weight: 1,11 kg



Type of height adjustability: vertically adjustable upper section

Length:246 mmWidth:200 mmHeight:54 mmPackaging dimension:lengthPackaging dimension:widthPackaging dimension:height

Tank/drain body

Number of outlets: 1
Material of drain body: ABS

Coverage features

Type of cover: Design cover

Cover material: Stainless steel 14301

Colour of cover: silver
Width of cover: 120 mm
Height of cover: 16 mm
Length of cover: 120 mm
Surface: ground

Frame material: Stainless steel 14301

Locking: Lock & Lift
Load class: L 15 (EN 1253-1)

Grating design: Kessel

Slip resistance class: R9 according to DIN 51130; C according to DIN

51097

Rim width: 132 mm
Rim length: 132 mm
Shape of upper section: square
Upper section material: ABS