


## Practicus drain body DN 50, Vertical outlet



### Article information

Item no.: 45250  
 GTIN: 4026092033579  
 Price group: 10

### Advantages

- Hygiene: hygienic, absolutely corrosion-free and durable material
- absolutely corrosion-free and durable material
- Fire protection: combinable with the Fire-Kit for fire and smoke protection

### Description

In combination with an upper section, the Practicus polymer drain body is used for point drainage and is equipped with a removable odour trap and a temporary protective cover. The drain meets particular sound insulation requirements in accordance with the measurements of the Fraunhofer Institute in Stuttgart.

#### Variant

System: 125  
 Waterproofing layer on the upper section: Connection flange  
 Waterproofing layer on the drain body: Connection flange  
 Sealing water height: 50 mm

#### General characteristics

Standard: EN 1253-1  
 Nominal size (DN): 50  
 Outer diameter (OD): 50 mm  
 Approval: Z-19.53-2414, Z-19.53-2414\_V, Z-19.17-1719, Z-19.17-1719\_V  
 Odour trap: included

#### Dimensions

Net weight: 0,59 kg  
 Gross weight: 0,7 kg  
 Diameter: 135 mm

Height:	191 mm
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height
Tank/drain body	
Number of outlets:	1
Material of drain body:	PP
Socket version:	vertical