


## Practicus drain body Press. fl., DN 50, Vertical outlet





## Article information

Item no.: 45259

GTIN: 4026092033807

Price group: 10

## **Advantages**

- Hygiene: hygienic, absolutely corrosion-free and durable material
- absolutely corrosion-free and durable material
- Fire protection: combinable with the Fire-Kit for fire and smoke protection

## **Description**

In combination with an upper section, the Practicus polymer drain body is used for point drainage and is equipped with a removable odour trap and a temporary protective cover. The drain meets particular sound insulation requirements in accordance with the measurements of the Fraunhofer Institute in Stuttgart.

Variant

System: 125

Waterproofing layer on the drain body: Press sealing flange (suitable for creating

watertight seals)

Sealing water height: 50 mm

General characteristics

Nominal size (DN): 50 Outer diameter (OD): 50 mm

Approval: Z-19.53-2414,Z-19.53-2414\_V,Z-19.17-1719,Z-19.17-17

19 V

Odour trap: included

**Dimensions** 

Net weight: 1,77 kg
Gross weight: 2,06 kg
Diameter: 273 mm
Height: 207 mm



Packaging dimension: length Packaging dimension: width Packaging dimension: height

Tank/drain body

Number of outlets: 1
Material of drain body: PP

Socket version: vertical