

Roof drain Press. fl., DN 100, with leaf trap



Article information

Item no.: 45950
GTIN: 4026092001318
Price group: 10

Description

The roof drain for flat roof surfaces is used for point drainage and is equipped with a pressure sealing flange as well as a gravel trap. The recyclable composite material Ecoguss fulfils the highest sound protection requirements, is resistant to aggressive media, can withstand temperatures up to 400 degrees Celsius and has a permanently corrosion-free surface. Note:

Please consult the KESSEL Service Centre for trapezoidal roof areas greater than 2500 sqm.

Variant	100
System:	without
Heating:	Press sealing flange (suitable for creating watertight seals)
Waterproofing layer on the drain body:	
General characteristics	
Nominal size (DN):	100
Outer diameter (OD):	110 mm
Dimensions	
Net weight:	0,92 kg
Gross weight:	1,11 kg
Diameter:	246 mm
Cutout dimension, width:	180 mm
Cutout dimension, length:	180 mm
Length:	246 mm
Width:	246 mm
Height:	182 mm
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height
Tank/drain body	

Material of drain body: PP

Coverage features

Type of cover: Leaf trap
Cover material: Polymer
Colour of cover: black
Width of cover: 120 mm
Height of cover: 80 mm
Length of cover: 120 mm
Shape of upper section: round
Upper section material: PP