

Roof drain Double press fl., DN 100, with leaf trap



Article information

Item no.: 45970
GTIN: 4026092029718
Price group: 10

Description

The roof drain for flat roof surfaces is used for point drainage and is equipped with a pressure sealing flange as well as a gravel trap. The recyclable composite material Ecoguss fulfils the highest sound protection requirements, is resistant to aggressive media, can withstand temperatures up to 400 degrees Celsius and has a permanently corrosion-free surface. Note:

Please consult the KESSEL Service Centre for trapezoidal roof areas greater than 2500 sqm.

Variant

100

System:

without

Heating:

Press sealing flange (suitable for creating watertight seals)

Waterproofing layer on the drain body:

General characteristics

100

Nominal size (DN):

110 mm

Outer diameter (OD):

Dimensions

40 - 80 mm

Vertical adjustment:

2,34 kg

Net weight:

3,1 kg

Gross weight:

246 mm

Diameter:

180 mm

Cutout dimension, width:

180 mm

Cutout dimension, length:

vertically adjustable upper section

Type of height adjustability:

246 mm

Length:

246 mm

Width:

length

Packaging dimension:

width

Packaging dimension:

height

Tank/drain body

Material of drain body:

PP

Coverage features

Type of cover:

Leaf trap

Cover material:

Polymer

Colour of cover:

black

Width of cover:

120 mm

Height of cover:

80 mm

Length of cover:

120 mm

Shape of upper section:

round

Upper section material:

PP