

Upper section, Linearis Compact L: 1150 mm, Sys 100, 304 SST cover, K3



Article information

Item no.: 47812S

GTIN: 4026092079942

Price group: 10

Advantages

- Individual design with reversible stainless steel
- Low installation depth
- Ready-to-install complete set

Description

Used in combination with a drain body of the KESSEL 100 modular system, the Linearis Compact upper section is suitable for use as indoor linear drainage.

Variant

100 System: Seepage opening: yes

Waterproofing layer on the upper section: Enclosed sealing collar to be glued (bd) according to

DIN 18534

Water exposure class in accordance to DIN

W3-I 18534-1 (up to and including): Sealing water height: 50 mm

Discharge rate (l/s) with 10 mm threshold: 0.6 Discharge rate (l/s) without threshold: 0,5 mm

General characteristics

100 Nominal size (DN): Outer diameter (OD): 100 mm Odour trap: included

Dimensions

Net weight: 2,62 kg Gross weight: 3,9 kg Outer dimension, length: 1215 mm Installation depth: 80 - 140 mm Width: 136 mm Height: 77 mm Packaging dimension: lenath Packaging dimension: width Packaging dimension: height



Coverage features

Type of cover: Stainless steel cover Cover material: Stainless steel 14301

Colour of cover: silver

Frame material: Stainless steel 14301

Load class: K 3 (EN 1253-1)
Grating design: optionally tileable

Rim width: 66 mm
Rim length: 1150 mm
Upper section material: ABS