

Scada wall drain w/cov, conc, fixed w/prf membrn



Article information

Item no.: 48000.01M GTIN: 4026092079119

Price group: 10

Advantages

- Flexible & convenient installation options
- Membrane flange attached in the factory
- Alternative odour trap Multistop

Description

The Scada wall drain is suitable for indoor floor drainage and provides connection options at the front, left and right-hand side.

Variant

Lighting: without

Waterproofing layer on the drain body: Factory-fitted sealing collar (WaD) according to DIN

18534 W3-I

Water exposure class in accordance to DIN

18534-1 (up to and including):

Sealing water height: 22 mm Discharge rate (l/s) with 20 mm threshold: 0,5

General characteristics

Nominal size (DN): 50
Outer diameter (OD): 58 mm
Odour trap: included

Dimensions

Net weight: 1,8 kg Gross weight: $2,31 \, \text{kg}$ Length: 362 mm Width: 195 mm 353 mm Height: Packaging dimension: length Packaging dimension: width Packaging dimension: height

Tank/drain body

Number of outlets: 1
Material of drain body: ABS



Coverage features

Type of cover: Scada drain cover

Colour of cover:selectableHeight of cover:61 mmLength of cover:296 mmMin. flooring height:15 mm

Frame material: Stainless steel 14301

Locking:insertedGrating design:InvisibleMax. flooring height:15 mmShape of upper section:squareUpper section material:ABS