


Ecoguss drain body DN 50, Vertical outlet



Article information

Item no.: 48458
GTIN: 4026092033289
Price group: 40

Advantages

- High-tech Ecoguss composite material
- Highest fire protection standards
- Scientifically confirmed sound protection effect

Description

The Ecoguss base body is used in combination with an attachment piece for point drainage, and is equipped with a removable odor trap, and a protective cover for the construction period. The recyclable composite material Ecoguss meets the highest noise protection requirements, is temperature-resistant, resistant to aggressive media, and has a permanently corrosion-free surface. It is also briefly flammable from 100 to 400 degrees Celsius. The outlet socket is suitable for connection to SML cast iron pipes. Separate equipotential bonding is not necessary.

Variant

System: 125
Waterproofing layer on the drain body:
Sealing water height: Connection flange
50 mm

General characteristics

Standard: EN 1253-1
Nominal size (DN): 50
Outer diameter (OD): 58 mm
Approval: Z-19.53-2414,Z-19.53-2414_V,Z-19.17-1719,Z-19.17-1719_V
Odour trap: included

Dimensions

Net weight: 0,91 kg
Gross weight: 1,02 kg
Diameter: 135 mm

Height: 191 mm
Packaging dimension:
Packaging dimension:
Packaging dimension:

Tank/drain body
Number of outlets: 1
Material of drain body: Ecoguss resistant
Socket version: vertical