


Ecoguss drain body DN 70, Vertical outlet



Article information

Item no.: 48478
 GTIN: 4026092033296
 Price group: 40

Advantages

- High-tech Ecoguss composite material
- Highest fire protection standards
- Scientifically confirmed sound protection effect

Description

The Ecoguss base body is used in combination with an attachment piece for point drainage, and is equipped with a removable odor trap, and a protective cover for the construction period. The recyclable composite material Ecoguss meets the highest noise protection requirements, is temperature-resistant, resistant to aggressive media, and has a permanently corrosion-free surface. It is also briefly flammable from 100 to 400 degrees Celsius. The outlet socket is suitable for connection to SML cast iron pipes. Separate equipotential bonding is not necessary.

Variant

System: 125
 Waterproofing layer on the drain body: Connection flange
 Sealing water height: 50 mm

General characteristics

Standard: EN 1253-1
 Nominal size (DN): 70
 Outer diameter (OD): 78 mm
 Approval: Z-19.53-2414, Z-19.53-2414_V, Z-19.17-1719, Z-19.17-1719_V
 Odour trap: included

Dimensions

Net weight: 0,93 kg
 Gross weight: 1,04 kg
 Diameter: 135 mm

Height: 201 mm
Packaging dimension:
Packaging dimension:
Packaging dimension:

Tank/drain body
Number of outlets: 1
Material of drain body: Ecoguss resistant
Socket version: vertical