

Parking deck drain, Ecoguss DN 125, round, Connection polymer pipe



Article information

Item no.: 48504
GTIN: 4026092036136
Price group: 40

Advantages

- Breakproof & load resistant
- withstand temperatures up to 400 degrees Celsius

Description

The Ecoguss parking deck drain is used for point drainage and is equipped with a sludge bucket. The recyclable composite material Ecoguss is temperature resistant and has a permanently corrosion-free surface. The outlet socket is suitable for connection to SML cast iron pipes. Separate equipotential bonding is not necessary. For products with pressure sealing flange:

The pressure sealing flange with bolts and screws made of stainless steel is used for the clamping or welding of bitumen and polymer bitumen sheets as well as for polymer and elastomer sealing sheets. Only membranes tested by the manufacturer may be used for watertight seals. The outlet socket is suitable for connection to SML cast iron pipes. With connection option for equipotential bonding. It can be exposed to flames for short periods, 100 up to 400 degrees Celsius.

Variant

System:

Contents of sludge trap:

Waterproofing layer on the drain body:

Discharge rate (l/s) with 20 mm threshold:

125

yes

Connection flange

4,5

General characteristics

Standard:

EN 1253-2

Nominal size (DN):

125

Outer diameter (OD):

125 mm

Dimensions

Net weight:

2,37 kg

Gross weight:

2,75 kg

Diameter:

290 mm

Cutout dimension, width:

300 mm

Cutout dimension, length:

300 mm

Length:

290 mm

Width:

290 mm

Height:

196 mm

Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height
Tank/drain body	
Material of drain body:	Ecoguss Heavy Duty
Socket version:	vertical
Coverage features	
Type of cover:	Round slotted cover
Cover material:	Ecoguss
Colour of cover:	black
Width of cover:	234 mm
Length of cover:	234 mm
Surface:	EDM
Frame material:	Ecoguss
Locking:	Lock & Lift
Load class:	B 125 (EN 124)
Rim width:	247 mm
Rim length:	247 mm
Shape of upper section:	round
Contents of sludge trap:	yes