


## Ecoguss drain body glued flange, DN 80, Horizontal outlet





## **Article information**

Item no.: 48583

GTIN: 4026092033364

Price group: 40

## **Advantages**

- High-tech Ecoguss composite material
- Highest fire protection standards
- Scientifically confirmed sound protection effect

## **Description**

The Ecoguss base body is used in combination with an attachment piece for point drainage, and is equipped with a removable odor trap, and a protective cover for the construction period. The recyclable composite material Ecoguss meets the highest noise protection requirements, is temperature-resistant, resistant to aggressive media, and has a permanently corrosion-free surface. It is also briefly flammable from 100 to 400 degrees Celsius. The glued flange with bolts and screws made of stainless steel is used for the clamping or welding of bitumen and polymer bitumen sheets as well as for polymer and elastomer sealing sheets. Only the sealing sheets tested by the manufacturer may be used for watertight seals. The outlet socket is suitable for connection to SML cast iron pipes. Separate equipotential bonding is not necessary.

Variant

System: 125

Waterproofing layer on the drain body:

Adhesive flange (suitable for moisture barriers)

Sealing water height: 50 mm

General characteristics

Standard: EN 1253-1

Nominal size (DN): 80
Outer diameter (OD): 83 mm
Odour trap: included

Dimensions

Net weight: 1,23 kg



Gross weight: 1,73 kg
Diameter: 348 mm
Height: 145 mm
Packaging dimension: length
Packaging dimension: width
Packaging dimension: height

Tank/drain body

Number of outlets: 1

Material of drain body: Ecoguss resistant

Socket version: lateral